



Spicer Infield Service Specifications



Contents

| | |
|---|--|
| 3 | Dana Australia Sales & Customer Service Contact List |
| 4 | Drive Axle Input & output shaft end play Crown wheel backlash Input/output shaft nut torque |
| 5 | Steer Axle King pin bush wear limits King pin clearance Tie rod end clearance Draw key nut torque |
| 6 | Driveshaft Universal joint movement Slip joint movement Driveline run out Retaining bolt torque |
| 7 | Notes |

This information is to be used in conjunction with the appropriate service manual. Dana Spicer service manuals can be found at www.spicerparts.com



Dana Australia Sales & Customer Service Contact List

Brad Wolstenholme
Head of Sales & Marketing

+61 418 972 143
brad.wolstenholme@dana.com

Commercial Vehicle

Paul French
Sales Manager – Commercial Vehicle

+61 408 136 824
paul.french@dana.com

Jock Pickford
Fleet & Area Manager – Commercial Vehicle

+61 408 571 498
jock.pickford@dana.com

Customer Service & General Information

**Suzanne Westwell,
Nicole Noy or
Vivian Cameron**

1300 00 DANA
aus.spicer@dana.com

Aftermarket

Shane Carey
Customer Support Manager

+61 438 559 385
shane.carey@dana.com

Jagath Dharmabandu
Aftermarket Program Manager

+61 419 499 436
jagath.dharmabandu@dana.com

John Ramsey
Business Development – Aftermarket
+61 425 777 915
john.ramsey@dana.com

Michael Parker
Business Development – Aftermarket

+61 418 962 060
michael.parker@dana.com

Warren Farrugia
Business Development – Aftermarket

+61 408 308 995
warren.farrugia@dana.com



brevini

Drive Axle

| Component Being Inspected | Dana Specification |
|---|---------------------------------------|
| D170 / D190 Input Shaft End Play | 1 to 5 Thou / 0.025 to 0.127mm |
| DSH40P Input Shaft End Play | 3 to 14 Thou / 0.076 to 0.355mm |
| D170 / D190 Output Shaft End Play | 1 to 45 Thou / 0.025 to 1.14mm |
| DSH40P Output Shaft End Play | 1 to 15 Thou / 0.025 to 0.381mm |
| D170 / D190 Crownwheel & Pinion Backlash | 8 to 18 Thou / 0.152 to 0.457mm |
| DSH40P Crownwheel & Pinion Backlash | 6 to 18 Thou / 0.152 to 0.457mm |
| D170 / D190 Input Nut Torque | 800 to 1000 Lbs.Ft / 1085 to 1355 Nm. |
| D170 / D190 Output Nut Torque | 800 to 1000 Lbs.Ft / 1085 to 1355 Nm. |
| R170 / R190 Rear / Rear Pinion Nut Torque | 800 to 1000 Lbs.Ft / 1085 to 1355 Nm. |
| DSH40P Input Nut Torque | 840 to 1020 Lbs.Ft / 1140 to 1383 Nm. |
| DSH40P Output Nut Torque | 680 to 832 Lbs.Ft / 920 to 1130 Nm. |
| RSH40 Rear / Rear Pinion Nut Torque | 575 to 703 Lbs.Ft / 780 to 953 Nm. |



Steer Axle

| Component Being Inspected | Dana Specification |
|--|---------------------------------------|
| Upper & Lower King Pin Bushes (All Models) | 15 Thou / 0.38mm Replace if in Excess |
| Kingpin Vertical Clearance (All Models) | 40 Thou / 1.016mm Max. |
| Tie Rod End Movement (All Models) | Axial & Radial 60 Thou / 1.524mm Max |
| Tie Rod Slotted Nut Torque (All Models) | 120 to 160 Lbs.Ft / 163 to 217 Nm |
| Straight Tie Rod Clamp Nut Torque (All Models) | 45 to 60 Lbs.Ft / 61 to 81 Nm |
| Drop Tie Rod Clamp Nut Torque (I & E Series) | 55 to 70 Lbs.Ft / 75 to 95 Nm |
| Drop Tie Rod Clamp Nut Torque (D2000F) | 150 to 180 Lbs.Ft / 203 to 244 Nm |
| Dual Draw Key Nut Torque (E1322i / E1462i) | 24 to 36 Lbs.Ft / 33 to 49 Nm |
| Single Draw Key Nut Torque (E1320i / E1460i) | 30 to 45 Lbs.Ft / 41 to 61 Nm |
| Single Draw Key Nut Torque (I140) | 25 to 31 Lbs.Ft / 34 to 42 Nm |



Driveshaft

| Component Being Inspected | Component Being Inspected |
|---|-----------------------------|
| Universal Joint Movement All Models | 6 Thou / .15mm Max |
| Slip Joint Spline Movement 10 Series & SPL | 0 to 12 Thou / 0 to 0.304mm |
| Slip Joint Spline Movement Compact Series | 0 to 7 Thou / 0 to 0.170mm |
| Driveline Run Out (Tube Yoke End) 3 Inches from weld | 20 Thou / .500mm |
| Driveline Run Out (Centre of Tube) | 15 Thou / .381mm |
| Driveline Run Out (Stub Shaft End) Neck of Slip Shaft | 5 Thou / .127mm |
| Strap Bolt Torque (SPL170 & 250 Series) | 115 Lbs. Ft / 156 Nm |
| Spring Tab Bolts (SPL170 & 250 Series) | 28 Lbs.Ft / 38 Nm |
| Strap Bolt Torque (10 Series) Pressed Metal Strap | 125 Lbs.Ft / 170 Nm |
| Strap Bolt Torque (10 Series) Cast Strap | 125 Lbs.Ft / 170 Nm |
| Bearing Plate Serrated Head Bolt Torque (10 Series) | 43 Lbs.Ft / 58 Nm |



Notes



Dana Australia
8 Hudson Court, Keysborough VIC 3173
Phone: 1300 00 DANA
www.dana.com.au

Copyright Dana Australia 2019
All rights reserved. Dana Australia.
Published in Australia,